

LumberJack Fastener

Part#	Length	Thread Length	Packaged	Package Weight/lbs.
TIM-6000	6"	2 1/2"	250/pail	16
TIM-8000	8"	2 1/2"	250/pail	20
TIM-10000	10"	2 1/2"	250/pail	25
TIM-12000	12"	2 1/2"	250/pail	30
TIM-14000	14"	2 1/2"	250/box	34
TIM-16000	16"	2 1/2"	250/box	39

One T-Driver Bit (T-40) included in each package

Note: All tests were conducted by an independent testing laboratory. Results of these tests are offered only as a guide and are not guaranteed in any way by **TRUFAST CORPORATION**. The quality of materials being anchored to will determine the designated values. **TRUFAST CORPORATION** recommends that pull-out tests be conducted to verify that the substrate provides adequate pull-out values. A safety factor of 4:1 or 25% of ultimate pull-out value is generally accepted as a safe workload. However, codes for specific safe working ratios may differ, and this is the responsibility of the purchaser or end user to obtain this information. Performance of LumberJack® fasteners will vary in different timbers.

Fastener Specifications

Thread Diameter:
.260
Shank Diameter:
.204
Head Style:
Flat

Installation Instructions:

For best performance
use a
1/2" high torque
drill-450RPM's.
Counter sink no more
than 1/2".



TRUFAST CORPORATION
02105 Williams Cty. Rd. 12-C
Shipping: S.R. #2 and U.S. Hwy. #6
Bryan, Ohio 43506-9804
1-800-443-9602 • 419-636-6715
Fax: 419-636-1784
WebSite: www.trufast.com
E-mail: trufast@bright.net



LumberJack Fastener

If you are working with logs, beams, or timbers, TRUFAST's LumberJack Fastener gives you top performance.

Easy to install, the LumberJack Fastener speeds through the wood using its relief wings and lubricant coating to outperform any fastener in the industry. The TRUFAST T-Drive (6 LOBE) is the most positive drive available. Below are features and benefits that highlight our LumberJack Fastener:

- Flat head style counter sinks easily
- 6 LOBE Drive
- One T-40 Driver bit per pail
- No predrilling needed
- Replaces the need for spikes and lagbolts, saves time
- Available in lengths of 6" - 16"
- Relief wings reduce driving torque and prevent drive bit cam out
- Lubricant coating reduces drill times and installed torque
- Packed in plastic pails for ease of handling and assures dry product
- Tru-Kote™ coating (black) exceeds FM4470 corrosion standard and withstands 30 cycles of the Kesternich DIN 50018 SFW 2.0 test and a 1000 hour salt spray ASTM B117 test

LumberJack Fastener

